

# Archlinux

## Hilfe

- <https://wiki.archlinux.org>
- <https://wiki.archlinux.de>
- <https://bbs.archlinux.org>
- <https://bbs.archlinux.de>

## X Starten ohne Displaymanager

<https://bbs.archlinux.org/viewtopic.php?pid=971168#p971168>

```
# --- window manager ---
# i.e. usage: WM=ob startx for openbox

DEFAULT_SESSION=i3
case $WM in
  ob)
    dbus-launch --exit-with-session openbox-session
    ;;

  *)
    dbus-launch --exit-with-session $DEFAULT_SESSION
    ;;
esac
```

## Home directory organisieren

[http://www.splitbrain.org/blog/2008-02/27-keeping\\_your\\_home\\_directory\\_organized](http://www.splitbrain.org/blog/2008-02/27-keeping_your_home_directory_organized)

```
export TD="$HOME/tmp/`date +%Y-%m-%d`"
td(){
  td=$TD
  if [ ! -z "$1" ]; then
    td="$HOME/tmp/`date -d "$1 days" +%Y-%m-%d`";
  fi
  mkdir -p $td; cd $td
  unset td
}
```

# consolefont wird nicht umgestellt

Grafikkartenmodul vor dem boot hook laden

in `/etc/mkinintcpio.conf`

```
MODULES=" radeon "
```

From:

<https://g6r.de/dw/> - **g6r**

Permanent link:

<https://g6r.de/dw/linux:arch?rev=1390338706>

Last update: **2014-05-07 10:53**

