

Individuelle body id in typoscript

```
# überschreibt den gesetzten BODY-Tag
page.bodyTag >
# CObject vom Typ TEXT
page.bodyTagCObject = TEXT
# Die ID mit der die Seite gespeichert wird wird genommen (hierum wrappen
wir in der nächsten Zeile)
page.bodyTagCObject.field = uid
page.bodyTagCObject.wrap = <body id="meineid-|">
```

send-hook mit Datum in mutt

```
set record=+sent-`date +%Y`
```

ergibt sent-2013

```
set record=+sent-`date +%Y-%m`
```

ergibt sent-2013-01

countdown-script

countdown script

[countdown](#)

```
#!/bin/bash
#
#####
#####
#
# countdown : bash script to visually count down a specified number of
seconds
#
#####
#####
#
# This program is free software; you can redistribute it and/or
# modify it under the terms of the GNU General Public License
# as published by the Free Software Foundation; either version 2
# of the License, or (at your option) any later version.
#
```

```

# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program; if not, write to the Free Software
# Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA
# 02111-1307, USA.
#
#####
#####
#
MY_NAME=countdown
MY_VERSION=1.1
MY_RELDATE=2000-07-06
MY_AUTHOR_NAME="Roy Batty"
MY_AUTHOR_MAIL="roybatty@altavista.net"
#
#####
#####
#
STAMP=/tmp/.stamp.$USER.$$
#
function init_timer() {
  [ -f $STAMP.stop ] && rm -f $STAMP.stop 2>/dev/null
  echo S=`date +%s` >$STAMP
}
function run_timer() {
  while [ ! -f $STAMP.stop ]; do
    echo S=`date +%s` >$STAMP
    sleep 1
  done
  rm -f $STAMP $STAMP.stop
}
function stop_timer() {
  touch $STAMP.stop
}
function clean_exit() {
  stop_timer
  echo " "
  echo "Terminated."
  mplayer $HOME/.bin/Alarmclock-mechanical.ogg
  trap "" 0 1 3 5 9 15
  exit 0
}
function syntax_error() {
  cat <<-EOF 1>&2

      $MY_NAME $MY_VERSION ($MY_RELDATE) - bash script to visually count
down

```

```

Copyright 2000: $MY_AUTHOR_NAME <$MY_AUTHOR_MAIL>
Usage:

$0 [[h] m] s
    counts down h hours, m minutes and s seconds

EOF
exit 1
}
function get_diff() {
    let DIFF=0
    [ "$1" = "" -o "$4" != "" ] && syntax_error
    while [ "$1" != "" ]; do
        let p=0
        [ "$1" != "0" ] && ! let p=$1 2>/dev/null && syntax_error
        [ $p -lt 0 ] && syntax_error
        let DIFF=$DIFF*60+$p
        shift
    done
}
function display_nice() {
    local s=$1; local h=0; local m=0; ni=""
    [ $s -ge 3600 ] && let h=$[ s/3600 ] && let s=$[ s%3600 ]
    [ $s -ge 60 ] && let m=$[ s/60 ] && let s=$[ s%60 ]
    [ $h -lt 10 ] && ni="0"; ni="$ni$h:"
    [ $m -lt 10 ] && ni="{ni}0"; ni="$ni$m:"
    [ $s -lt 10 ] && ni="{ni}0"; ni="$ni$s"
    echo -n "$ni"
}
#
# main script
#
get_diff $*
trap clean_exit 0 1 3 5 9 15
echo "$MY_NAME $MY_VERSION ($MY_RELDATE) - Counting down `display_nice
$DIFF` [hrs:min:sec]"
if [ $DIFF -le 0 ]; then
    echo "Nothing to do." 1>&2
    exit 2
fi
echo " Elapsed | Remaing. | Complete"
let START=`date +%s`
declare -a HASH=( [0]=". " [1]="o " [2]="0 " [3]="- " )
compl="#####"
blank=" "
let ha=0
init_timer
run_timer &
while true; do
    . $STAMP
    let R=$DIFF-$S+$START

```

```
if [ $R -gt 0 ]; then
  echo -n "${HASH[$ha]}`display_nice $[ $DIFF-$R ]` | `display_nice
$R` | "
  let P=$(( $S-$START ) * 100 / $DIFF )
  echo -ne "[${compl:0:P/2}${blank:0:50-P/2}] $P%\r"
else
  echo -n "${HASH[$ha]}`display_nice $DIFF` | `display_nice 0` | "
  echo -ne "[$compl] 100%\r"
  clean_exit
fi
let ha=$(( ha+1 ) % 4 )
sleep 1
done
```

Checksummen prüfen

```
md5sum -c md5sums 2> /dev/null | grep OK
```

From:

<https://g6r.de/dw/> - g6r

Permanent link:

<https://g6r.de/dw/tmp?rev=1384625360>

Last update: **2014-05-07 10:53**

